



AVADA1

is a vibration and surface temperature sensor



Applications

- Rotating machines
- Motor bearings
- Pumps
- Blowers
- Cooling tower fans

Specifications

Measurement data	Acceleration (peak), Velocity (RMS), Surface temperature Frequent range : 60-37,500 CPM
Measurement range	Acceleration range : 0-13.8 g Temperature range : -40 °C to +125 °C
Operating temperature	: 0 – 70 °C
Degrees of protection	: IP66
Wireless technology	: LoRa AS923 MHz (920- 925 MHz)
Dimension	: 54.00 (W) x 52.00 (D) x 95.40 (H)mm

Smart
Industrial Solutions



Mr. Thitipat Charoenkitsupat (Ball)
Sales Engineer

065 936 0775

Thithchar@scg.com



Ms. Supinya Supajam (Fan)
Manager - Smart Industrial Solutions


065 619 1536

Supinyas@scg.com

Contact Us



Total solution platform for your reliability



Benefit

- Low infrastructure cost
- Easy installation
- Intelligent dashboard
- Low power
- Anywhere monitoring
- High data security
- Wireless
- Compatible with any systems

Smart
Industrial Solutions

 **Mr. Thitipat Charoenkitsupat (Ball)**
Sales Engineer
 065 936 0775
 Thitchar@scg.com

 **Ms. Supinya Supajam (Fan)**
Manager - Smart Industrial Solutions
 065 619 1536
 Supinyas@scg.com

Contact Us

